The Files - Project 2151

17 March 1959

25X1A9a [redacted]

Conference Report - [redacted] 25X1A5a

1. On 5 March 1959, a conference was held in Washington, D.C., with the local representative of [redacted]. Present at 25X1A5 the conference were the following:

25X1A5a1 [redacted]

25X1A9a [redacted] - OC-E/R+D-EP

25X1A5a1 2. Since our last meeting [redacted] had obtained (at no cost to us) four samples of conducting glass. The conducting coating is applied in the form of a dipole antenna with silver conductors supplied at the terminals of the dipole. Physically the dipole configuration should be resonant to a frequency of about 800 mc. The elements are quite 25X1A3b wide which may adversely affect the performance of the coating when used as an antenna.

3. The main disadvantage of the conductive coating remains the [redacted]

25X1A5a1

25X1A5a1 4. Back in the 30's [redacted] did some investigation into the possibility of making a glass which was truly conducting throughout its volume. If we are interested in the results of the old investigations, [redacted] was offered to set up a meeting with the engineers at their 25X1A5a1 [redacted] plant for the purpose of discussing this research as well as the conductive coatings. [redacted] was told that we would contact him 25X1A5a1 about a conference in New York after we had investigated the characteristics of the sample antennas which he supplied. 25X1A

25X1A9a [redacted]

Distribution:
R+D Subject File / Monthly Report
SPS / R+D Lab
EP Chrono

OC-E/R+D-EP/[illegible] (17 March 1959)